

foot inserts for round tubing



ADJUSTABLE FOOT INSERTS FOR ROUND TUBING

Conventional Round & Hex Adjustable Toes For Round Tubing and Pipe

Available In:


- Natural Finish Zamak
- Nickel Plated Zamak
- Thermoplastic, Gray or Black
- Stainless Steel Clad



A10 & A11 SERIES ADJUSTABLE FOOT INSERTS FOR ROUND TUBING AND PIPE

APPLICATION	FOOT DESCRIPTION	TYPE	HEIGHT	ADJ.	MODEL NO.	LOAD RATING LBS/FOOT (Kg/Ft)	REF.
1" (25mm) O.D. TUBING 16 GA. (1.5mm) & 18 GA. (1.2mm)	NICKEL PLATED ZAMAK	HEX	11/16" (17.5mm)	13/16" (21mm)	A10-0221-C	1100 (500)	C
1-1/4" (32mm) O.D. TUBING 16 GA. (1.5mm)	NICKEL PLATED ZAMAK	HEX	3/4" (19mm)	1-1/8" (28mm)	A10-0421-C	1400 (635)	C
1-1/4" I.P.S. PIPE 1-1/2" (38mm) O.D. TUBING 16 GA. (1.5mm)	NATURAL FINISH ZAMAK	HEX	1-1/4" (32mm)	1-1/8" (28mm)	A10-0611-C	2000 (900)	D
	STAINLESS STEEL CLAD	HEX	1-1/2" (38mm)	1-1/4" (32mm)	A10-0651-C	2000 (900)	D
	THERMOPLASTIC BLACK	HEX	1-3/8" (35mm)	1-1/16" (27mm)	A10-0631-C	200 (90)	F
	THERMOPLASTIC GRAY	HEX	1-3/8" (35mm)	1-1/16" (27mm)	A10-0641-C	200 (90)	B
1-5/8" (41mm) O.D. TUBING 16 GA. (1.5mm)	NATURAL FINISH ZAMAK	HEX	1-1/4" (32mm)	1-1/8" (28mm)	A10-0811-C	2000 (900)	G*
	STAINLESS STEEL CLAD	HEX	1-1/2" (38mm)	1-1/4" (32mm)	A10-0851-C	2000 (900)	G*
	STAINLESS STEEL CLAD	ROUND	1-1/2" (38mm)	1-1/4" (32mm)	A10-0852-C	2000 (900)	A
	THERMOPLASTIC BLACK	HEX	1-3/8" (35mm)	1-1/16" (27mm)	A10-0831-C	200 (90)	F
	THERMOPLASTIC GRAY	HEX	1-3/8" (35mm)	1-1/16" (27mm)	A10-0841-C	200 (90)	B
2" (50mm) O.D. TUBING 16 GA. (1.5mm)	STAINLESS STEEL CLAD	HEX	1" (25mm)	2" (50mm)	A11-0851-C	2300 (1040)	E

* SHOWN WITH OPTIONAL POSI-GRIP LOCKING RING



SHOWN WITH OPTIONAL
LOCKING RING

*OPTIONAL POSI-GRIP LOCKING RING

MODEL NO.
A10-0010-C

SPRING STEEL WITH CLEATS THAT GRIP AND BITE TUBING TO LOCK FOOT TO TUBE. AVAILABLE FOR MODEL NO'S A10-0811-C, A10-0851-C AND A10-0852-C.

