



A14 & A15 SERIES ADJUSTABLE FOOT INSERTS For Square Tubing

- AVAILABLE IN STAINLESS STEEL, NICKEL PLATED ZAMAK OR NATURAL FINISH ZAMAK
- 2"(50mm) MODEL COMPLETE WITH RETAINING RING AND HEAVY-DUTY CONSTRUCTION



A14 & A15 SERIES ADJUSTABLE FOOT INSERTS FOR SQUARE TUBING

APPLICATION	FOOT DESCRIPTION	TYPE	HEIGHT	ADJ.	MODEL NO.	LOAD RATING LBS/FT(KG/FT)	REF.
1"(25mm) SQ. TUBING 16 GA. (1.5mm) OR 18 GA. (1.2mm)	NICKEL PLATED ZAMAK	HEX	11/16" (17.5mm)	7/8" (22mm)	A14-0221-C	1200 (550)	A
1-1/4"(32mm) SQ. TUBING 16 GA. (1.5mm) OR 18 GA. (1.2mm)	NATURAL FINISH ZAMAK	HEX	1-1/4" (32mm)	1-1/8" (28mm)	A14-0411-C	2000 (900)	B
	NICKEL PLATED ZAMAK	HEX	1-3/8" (35mm)	1" (25mm)	A14-0421-C	2000 (900)	
1-1/2"(38mm) SQ. TUBING 16 GA. (1.5mm) OR 18 GA. (1.2mm)	NATURAL FINISH ZAMAK	HEX	1-1/4" (32mm)	1-1/8" (28mm)	A14-0611-C	2000 (900)	C
	STAINLESS STEEL CLAD	HEX	1-1/2" (38mm)	1-1/8" (28mm)	A14-0651-C	2000 (900)	
2"(50mm) SQ. TUBING 16 GA. (1.5mm)	STAINLESS STEEL CLAD	HEX	1" (25mm)	2" (50mm)	A15-0851-C	2300 (1040)	D

